








The 6000 CNG guarantees reduced sound emissions, eliminates the emission of fine particles into the atmosphere, as well as all types of pollution caused by the sweeper engine. In short, it is a truly zero emission machine for municipalities.



Thanks to the Dulevo patented mechanical-suction-filtering system, the Dulevo 6000 CNG sweeper has a performance three times higher than any other traditional sweeper. The collection is mechanical and is facilitated by the side brushes, which convey the debris toward the centre of the machine, where the cylindrical central brush then sends it at a high speed onto a vertical conveyor. The debris is loaded through the upper part in the refuse container, this way optimizing the loading capacity of the machine. The dust raised by the cylindrical central brush is sucked and kept in the refuse container thanks to the depression in the container itself created by two high-range and high-prevalence suction fans. The peculiar fabric filtering system retains even the thinnest particulates and completes the sweeping cycle, guaranteeing the reintroduction in the environment of clean air only.







In cooperation with Gore® Dulevo developed the only worldwide existing full fine dust filtration sweeper. This mechanical-suction filtration system grants with the exclusive application of the Gore® technology a total abatement of PM10 particles.

Further benefits of the filter technology are:

- No maintenance
- Self cleaning effect
- Highest proofed absorbing of PM10 / PM5 / PM2,5 / PM 1
- Granted constant & durable filtering
- 35 % higher airflow
- Resistance against water, oil, fats, chemical agents, etc


GORE dust filters installed in the industrial sweeper have 5 YEARS warranty.





















The 180-degree full motion massive front brush is an indispensable auxiliary tool for sweeping corners, gutters and for increasing working width.


The hopper uplifting system allows the discharge of the debris in refuse containers, trucks or in big refuse compactors.

A variety of options expand the working spectrum of Dulevo 6000 CNG everywhere at any time.











Technical data		6000CNG
Sweeping width		
- With central brush	mm	1300
- With central brush and side brushes	mm	2600
- With central, side brushes and third brush	mm	3500
Container volume	m³	4,8
Dumping height (OPT.)	mm	1150 (2300)
Seats in the cabin	n°	3
Cleaning performance	m²/h	105.000
Maximum speed	Km/h	25 - 42
Steering diameter (kerb to kerb)	mm	9360
Certification PM		PM 2,5/PM10****
Engine Brand		FPT industrial (Iveco)
Engine Emissions		EURO 6 STEP C
Fuel		CNG





Dulevo International S.p.A. Via Giovannino Guareschi, 1 43012 Fontanellato (PR) Italia Tel: +39-0521-827711



8

Fax: +39-0521-827795

www.dulevo.com

